

Tahiti


Average score 85%

Highest 146%
Lowest 48%

Practical effect to be expected of SolarDrive S2E (200 W)

Trail type - golf course			Light	Medium	Heavy
Consumption	18 holes	kWh	0,80	1,10	1,60
Power production	High (best month)	kWh	1,17	1,17	1,17
PRP* supplied by SolarDrive S2E	High (best month)	kWh	146%	106%	73%
Power production	Low (weakest month)	kWh	0,77	0,77	0,77
PRP* supplied by SolarDrive S2E	Low (weakest month)	kWh	96%	70%	48%
Power production	Yearly Average	kWh	0,94	0,94	0,94
PRP* supplied by SolarDrive S2E	Yearly Average	kWh	117%	85%	59%

*Percentage of Required Power



Basic data


Nominal effect	kW	0,200											Lat.	-17,3	Lon.	-149
Solar insolation		Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Average		
kWh/m2/day**		6,63	6,43	6,24	5,43	4,55	4,36	4,59	5,31	6,11	6,45	6,64	6,07	5,73		
Avg. day temperature (C)		28,0	28,1	28,4	28,2	27,7	26,9	26,4	26,1	26,1	26,4	26,8	27,5	27,2		
Avg. day temperature (F)		82,4	82,6	83,1	82,8	81,9	80,4	79,5	79,0	79,0	79,5	80,2	81,5	81,0		
Temperature loss factor		0,93	0,93	0,93	0,93	0,93	0,93	0,94	0,94	0,94	0,94	0,93	0,93	0,87		
System loss factor		0,94	0,94	0,94	0,94	0,94	0,94	0,94	0,94	0,94	0,94	0,94	0,94	0,94		
Expected output kWh		1,16	1,13	1,09	0,95	0,80	0,77	0,81	0,94	1,08	1,13	1,17	1,06	0,94		

Percentage of consumption driving 18 golf holes on

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Average
Light trail	145%	141%	136%	119%	100%	96%	101%	117%	134%	142%	146%	133%	117%
Medium trail	105%	102%	99%	86%	72%	70%	73%	85%	98%	103%	106%	97%	85%
Heavy trail	73%	70%	68%	59%	50%	48%	50%	58%	67%	71%	73%	67%	59%

Additional golf holes using SolarDrive on Top

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Average
Light trail	26	25	25	21	18	17	18	21	24	26	26	24	21
Medium trail	19	18	18	16	13	13	13	15	18	19	19	17	15
Heavy trail	13	13	12	11	9	9	9	11	12	13	13	12	11



Potential CO2 savings/car/year* 170 to 291 kilos or 374 to 642 lbs.**

**Source: NASA Langley Research Center Atmospheric Science Data Center (22 year average)

***CO2 savings are calculated compared to grid electricity supplied from modern power plants burning fossil fuels (0.49-0.85 kg CO2/kWh)

****If battery charge level is low from the start the S2E must be allowed the necessary time to charge as the energy is accumulated over the day

Disclaimer:

SolarDrive takes no responsibility for the correctness of the basic data obtained from NASA nor for the actual experienced results. The figures above is presented as a guideline only. The actual result may be influenced by many other factors as well e.g. length of course, battery watering, altitude, time of year, time of day, present weather conditions, local shades from houses, trees, mountains, tire inflation, general maintenance etc.